

- 1.一體拉伸成型支架。
- 2.雙波盤結構。

- 材質：雙軸塑芯方邊TPR輪
- 用途：工業、物流台車、重型機械設備、常用於各式推車及台車

1. One-piece stretch forming bracket.
2. Double wave disk structure.

- Material: Double axis plastic core square edge TPR wheel
- Uses: Industrial, logistics trolleys, heavy machinery and equipment, often used in various trolleys and trolleys.



[JZ-304-1S]



[JZ-304-1R]



[JZ-304-2S]



[JZ-304-3S]



[JZ-304-1H]



[JZ-304-2H]



[JZ-304-3H]



[JZ-304-1G]



[JZ-304-2G]



[JZ-304-3G]



[JZ-304-1K]



[JZ-304-2K]



[JZ-304-3K]



[JZ-304-1D]



[JZ-304-2D]



[JZ-304-3D]

| 商品型號        | 輪子  | 輪徑  | 輪寬 | 安裝高度 | 底板尺寸  | 孔距    | 孔徑  | 荷重 (KG) |
|-------------|-----|-----|----|------|-------|-------|-----|---------|
| JZ-304-1-1_ | TPR | 63  | 25 | 92   | 95*66 | 75*45 | 8.5 | 75      |
| JZ-304-1-2_ |     | 75  |    | 108  |       |       |     | 85      |
| JZ-304-1-3_ |     | 100 |    | 130  |       |       |     | 110     |
| JZ-304-1-4_ |     | 125 |    | 159  |       |       |     | 135     |
| JZ-304-1-5_ |     | 150 |    | 181  |       |       |     | 140     |

\*JZ-304-1系列可選配R固定/S活動/H煞車/G鐵煞/K疊煞/D邊煞\*

| 商品型號        | 輪子  | 輪徑  | 輪寬 | 安裝高度 | 牙桿尺寸   | 荷重 (KG) |
|-------------|-----|-----|----|------|--------|---------|
| JZ-304-2-1_ | TPR | 63  | 32 | 92   | M12*30 | 65      |
| JZ-304-2-2_ |     | 75  |    | 108  |        | 75      |
| JZ-304-2-3_ |     | 100 |    | 130  |        | 100     |
| JZ-304-2-4_ |     | 125 |    | 159  |        | 125     |
| JZ-304-2-5_ |     | 150 |    | 181  |        | 140     |

\*JZ-304-2系列可選配S活動/H煞車/G鐵煞/K疊煞/D邊煞\*

| 商品型號        | 輪子  | 輪徑  | 輪寬 | 安裝高度 | 孔頂尺寸 | 荷重 (KG) |
|-------------|-----|-----|----|------|------|---------|
| JZ-304-3-1_ | TPR | 63  | 32 | 92   | Ø13  | 65      |
| JZ-304-3-2_ |     | 75  |    | 108  |      | 75      |
| JZ-304-3-3_ |     | 100 |    | 130  |      | 100     |
| JZ-304-3-4_ |     | 125 |    | 159  |      | 125     |
| JZ-304-3-5_ |     | 150 |    | 181  |      | 140     |

\*JZ-304-3系列可選配S活動/H煞車/G鐵煞/K疊煞/D邊煞\*