

平面導電TPR輪

Flat TPR wheel



JZ-306

商品介紹 Product description

- 1.一體拉伸成型支架。
- 2.雙波盤結構。

- 材質：雙軸塑芯方邊TPR輪
- 用途：工業、物流台車、重型機械設備、常用於各式推車及台車

1. One-piece stretch forming bracket.
2. Double wave disk structure.

- Material: Dual axis plastic core square edge TPR wheel
- Uses: Industry, logistics trolleys, heavy machinery and equipment, often used in various trolleys.



[JZ-306-1S]



[JZ-306-1R]



[JZ-306-1H]



[JZ-306-1G]



[JZ-306-1K]



[JZ-306-1D]



[JZ-306-2S]



[JZ-306-2H]



[JZ-306-2G]



[JZ-306-2D]



[JZ-306-3S]



[JZ-306-3H]



[JZ-306-3G]



[JZ-306-3D]

商品型號	輪子	輪徑	輪寬	安裝高度	底板尺寸	孔距	孔徑	荷重 (KG)
JZ-306-1-1_	TPR	63	32	92	95*66	75*45	8.5	75
JZ-306-1-2_		75		108				85
JZ-306-1-3_		100		130				110
JZ-306-1-4_		125		159				135
JZ-306-1-5_		150		181				140

JZ-306-1系列可選配R固定/S活動/H煞車/G鐵煞/K疊煞/D邊煞

商品型號	輪子	輪徑	輪寬	安裝高度	牙桿尺寸	荷重 (KG)
JZ-306-2-1_	TPR	63	32	96	M12*30	75
JZ-306-2-2_		75		112		85
JZ-306-2-3_		100		134		110
JZ-306-2-4_		125		163		135
JZ-306-2-5_		150		189		140

JZ-306-2系列可選配S活動/H煞車/G鐵煞/K疊煞/D邊煞

商品型號	輪子	輪徑	輪寬	安裝高度	孔頂尺寸	荷重 (KG)
JZ-306-3-1_	TPR	63	32	90	Ø13	75
JZ-306-3-2_		75		106		85
JZ-306-3-3_		100		128		110
JZ-306-3-4_		125		157		135
JZ-306-3-5_		150		183		140

JZ-306-3系列可選配S活動/H煞車/G鐵煞/K疊煞/D邊煞